



# SSB 331

---

## Product Data Sheet

Marketing Department.  
September 19, 2020

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website [www.ascensotyres.com](http://www.ascensotyres.com)

**Release Month:** September '20

**Brand:** ASCENSO

**Tread Pattern :** SSB 331

**Tyre Construction:** Bias

**Type :** Tubeless

**Main Applications:** Skid Steer

**TRA Code :** R-4

List of Sizes

Size	PR
23X8.50-12	8
26X12.00-12	12
27X8.50-15	8
27X10.50-15	8
31X15.50-15	10
10-16.5	8,10
12-16.5	10,12
33X15.50-16.5	12
14-17.5	14
15-19.5	14



## Salient Features

### **Deep Tread and Optimized Spaced Lugs:**

Ensures high traction & improves self cleaning abilities

### **Extra Strong Casing:**

Higher load carrying capacity in all application

### **Special Tread Compound:**

High tear and cut resistance in loading operations



# Technical Specification

Size	Recomm. Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)
		SW	OD					Speed (kmph) (mph)
		mm	mm					10
		inch	inch	inch	inch		psi	6
10-16.5	8.25	264	773	356	2312	8 PR	4.1	1880
		10.4	30.4	14	91	130 A2	60	4140
10-16.5	8.25	264	773	356	2312	10 PR	5.2	2140
		10.4	30.4	14	91	134 A2	75	4710
12-16.5	9.75	307	831	380	2486	10 PR	4.5	2550
		12.1	32.7	15	97.9	140 A2	65	5600
12-16.5	9.75	307	831	380	2486	12 PR	5.5	2900
		12.1	32.7	15	97.9	145 A2	80	6393
33X15.50-16.5	12	394	840	383	2522	12 PR	4.1	3150
		15.5	33.1	15.1	99.3	148 A2	59	6940
14-17.5	10.5	349	921	419	2755	14 PR	5.5	3880
		13.7	36.2	16.4	108.4	155 A2	80	8542

Size	Recomm. Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)
		SW	OD					Speed (kmph) (mph)
		mm	mm					40
		inch	inch	inch	inch		psi	25
23X8.50-12	7	213	574	263	1717	8 PR	3.4	550
		8.4	22.6	10.4	67.6	87 A8	49	1200
26X12.00-12	10.5	307	655	297	1967	12 PR	5.4	1180
		12.1	25.8	11.7	77.4	114 A8	78	2600
27x8.50-15	7	213	678	313	2028	8 PR	4.2	850
		8.4	26.7	12.3	79.8	102 A8	61	1870
27x10.50-15	8.5	259	691	318	2067	8 PR	4.2	930
		10.2	27.2	12.5	81.4	105 A8	61	2040
31x15.50-15	13	391	792	360	2369	10 PR	4.2	1660
		15.4	31.2	14.2	93.3	125 A8	61	3640
15-19.5	11.75	394	1019	464	3048	14 PR	4.8	3000
		15.5	40.1	18.3	120	146 A8	70	6600

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction, Material handling, Earthmover and Forestry.