

PRODUCT DATA SHEET

SCB 430

Tyre Construction: Bias

Type: Tube Type / Tube less

Main Applications: Smooth Compactor

TRA Code: IND



Salient Features:

Large Tread Area:

- High ground contact area.
- Uniform Compaction to road belts & asphalt.

Specially formulated Heat Resistant compound:

- Excellent performance at high operating temperature.
- Longer Tire life.



Technical Data



Size	Tyre Type	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommended load (kg) (lbs)	
			SW	OD					Speed (kmph) (mph)	
			mm	mm					10	15
			inch	inch					6	9
7.50-15	TT	6	215	790	359	2363	14 PR	8.8	2900	-
			8.5	31.1	14.1	93.0	145 A2	127	6380	-
8.5/90-15 K	TL	6	220	785	357	2348	6PR	3.5	1800	-
			8.7	30.9	14.1	92.4	128 A2	51	3960	-
9.5/65-15	TL	7	235	675	312	2059	6PR	3.3	1320	1060
			9.3	26.6	12.3	81.1	118 A2	47	2910	2340
10.5/80-16	TL	8	275	810	370	2471	6PR	4.5	1850	1500
			10.8	31.9	14.6	97.3	129 A2	65	4080	3310
9.00-20	TT	7.5	259	1016	464	3039	16PR	8.3	4750	-
			10.2	40.0	18.3	119.6	162 A2	120	10450	-
11.00-20	TT	8.5	298	1083	491	3300	18PR	8.3	5800	4625
			11.7	42.6	19.3	129.9	169 A2	120	12800	10200

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com